

SAN ANTONIO WATER SYSTEM
SAN ANTONIO, TEXAS

Specifications For Full Brim Safety Hard Hat

May 30, 2002

1. SCOPE

This specification covers all Safety Hard Hats worn by Personnel who are involved in indoor and outdoor activities in Treatment Plants, Heating & Cooling Plants, Operations Maintenance & Construction, including monitoring, maintenance and repair of SAWS distribution and collection systems located in all traffic areas and open field areas.

2. GENERAL REQUIREMENTS

ANSI Z89.1 – 1997 Type 1, Class E

Requirements: to include Impact, Penetration, and Electrical insulation.

Description:

Material: High-Density Polyethylene

Brim: Full Brim

Suspension: Four (4)-point minimum

Brow Pad: Foam-backed Vinyl or Microporite

Type: Sure-Lock Ratchet

Color:

Available in both Yellow and White

Accessories Description:

Chin Strap: Elastic, Adjustable

Neck Flap Shade: 100 % Cotton Fabric

Sun Shield: Attachable to the Brim

Replacement Suspension: Four (4)-point

Liners: Regular Length Cotton Twill

Long Neck Thinsulate

3. APPROVED MANUFACTURERS AND MODELS:

Manufacturer

Model

1. Mine Safety Appliances

MSA 475366 – Yellow

Mine Safety Appliances

MSA 475369 – White

2. Bullard

303 R – Yellow/White