

SAN ANTONIO WATER SYSTEM  
SAN ANTONIO, TEXAS

Specifications For Headband Earmuff (Hearing Protection)

August 8, 2002

Revised March 12, 2010

1. SCOPE

This specification covers the headband earmuff style hearing protection, use by Personnel who work where noise levels are above a TWA of 85 dB.

2. GENERAL REQUIREMENTS

OSHA 29 CFR 1910.95 (b)(1)

Subject Fit data ANSI S12.6-2002

Tested to ANSI S.3.19-1974

**Description:**

Headband earmuff designed to wear over the head and under a safety hard hat. Cup height at both ears and headband must be adjustable by the wearer. Capable of muffling high and low frequencies.

**Physical Property Data:**

**Headband:** Padded, extra long and wide.

**Muffs:** Soft foam cushions.

**Cushions:** Vinyl covered, soil resistant.

**Weight:** 10 oz. Maximum.

**Attenuation:** NRR, 31 dB minimum.

**Sizing of Headband:**

**Fully Adjustable**

**Accessories Description:**

Hygiene Kit (HK777): Containing cushions and foam inserts

**Special Notations:**

SAWS, at no cost to the manufacturer, may subject random units to testing by an independent laboratory for compliance with these specifications. Any visible defect or failure to meet the quality standards herein will be grounds for rejecting the entire order.

3. APPROVED MANUFACTURERS AND MODELS

Manufacturer

1. Howard Leight

Model

Leightning – L3